

# The Adler Gold Range

The Gold Range from Adlerac is its most popular rack and is the stalwart in the range. This popular rack was designed to industry standard DIN41494 specifications (sections 1 through 4). Its frame is constructed from toughened light weight extruded aluminium and finished with stylish and distinctive detailing. This compact rack is extremely modular in design and thus offers customers freedom of installed equipment and exceptional ease of use. Features include a quality SABS approved smoked and toughened glass door with lock; hinged side panels strengthened by its double bent edges and welded corners; raised top for ventilation; depth reducers; punched profiles and adjustable feet.



## 600mm x 600mm Aluminium Frame Rack

Part No.	Description	Width	Height	Depth
1R19-610	19" x 10U usable	600mm	650mm	600mm
1R19-613	19" x 13U usable	600mm	783mm	600mm
1R19-620	19" x 20U usable	600mm	1094mm	600mm
1R19-625	19" x 25U usable	600mm	1316mm	600mm
1R19-634	19" x 34U usable	600mm	1716mm	600mm
1R19-638	19" x 38U usable	600mm	1894mm	600mm
1R19-643	19" x 43U usable	600mm	2116mm	600mm
1R19-647	19" x 47U usable	600mm	2294mm	600mm

## 600mm x 800mm Aluminium Frame Rack

Part No.	Description	Width	Height	Depth
1R19-820	19" x 20U usable	600mm	1094mm	800mm
1R19-825	19" x 25U usable	600mm	1316mm	800mm
1R19-834	19" x 34U usable	600mm	1716mm	800mm
1R19-838	19" x 38U usable	600mm	1894mm	800mm
1R19-843	19" x 43U usable	600mm	2116mm	800mm
1R19-847	19" x 47U usable	600mm	2294mm	800mm

## 700mm x 800mm Aluminum Frame Rack

Part No.	Description	Width	Height	Depth
1R23-820	23" x 20U usable	700mm	1094mm	800mm
1R23-825	23" x 25U usable	700mm	1316mm	800mm
1R23-834	23" x 34U usable	700mm	1716mm	800mm
1R23-838	23" x 38U usable	700mm	1894mm	800mm
1R23-843	23" x 43U usable	700mm	2116mm	800mm
1R23-847	23" x 47U usable	700mm	2294mm	800mm

## 800mm x 800mm Aluminum Frame Rack

Part No.	Description	Width	Height	Depth
1R24-825	24" x 25U usable	800mm	1316mm	800mm
1R24-834	24" x 34U usable	800mm	1716mm	800mm
1R24-838	24" x 38U usable	800mm	1894mm	800mm
1R24-843	24" x 43U usable	800mm	2116mm	800mm
1R24-847	24" x 47U usable	800mm	2294mm	800mm